




LOL PLUS LOCK-ON HOSE

LOCK-ON

RECOMMENDED FOR Petroleum-based hydraulic oils, water, glycol anti-freeze solutions, engine lubricating oils, and air. Lock-On hose and couplings are NOT recommended for pressure surge applications or critical applications, such as permanent piping in residential or commercial buildings. Do not use for gasoline or diesel fuels, unless approved by Gates H/C Product Application.



TUBE Black, oil resistant, synthetic rubber highly resistant to oil and heat (Nitrile). See Hose Stock Characteristics.

REINFORCEMENT One fiber braid.

COVER Oil and abrasion resistant synthetic rubber (Nitrile and PVC). Available in black Polychloroprene (LOLA), blue (LOLB), green (LOLG), red (LOLR), yellow (LOLY) and gray (LOLC) colors.

TEMPERATURE RANGE -40°F to +212°F (-40°C to +100°C). For water emulsions see Temperature Limits Table.

PART DESCRIPTION	DN	ID (IN)	OD		WP		BURST		MBR		WEIGHT	
			IN	MM	PSI	MPA	PSI	MPA	IN	MM	LBS/FT	KG/M
3LOLA	5	3/16	0.41	10.4	300	2.1	1200	8.3	3.0	76	0.07	0.10
4LOLA	6	1/4	0.47	11.9	300	2.1	1200	8.3	3.0	76	0.08	0.12
5LOLA	8	5/16	0.55	14.0	300	2.1	1200	8.3	3.0	76	0.10	0.15
6LOLA	10	3/8	0.63	16.0	300	2.1	1200	8.3	3.0	76	0.13	0.19
8LOLA	12	1/2	0.77	19.6	300	2.1	1200	8.3	5.0	127	0.17	0.25
10LOLA	16	5/8	0.94	23.9	300	2.1	1200	8.3	6.0	152	0.23	0.34
12LOLA	19	3/4	1.06	26.9	300	2.1	1200	8.3	7.0	178	0.28	0.42

BRAIDED
SPIRAL
THERMOPLASTIC
OTHERS