



SMP-W600-HD (600 PSI)

Recommended For: Mandrel built lightweight air hose suitable for a variety of general purpose in industries, construction sites and mines.

Temperature Range: -4 °F to +185 °F (-20 °C to +85 °C)

Tube: Black SBR/NR Blend Rubber

Reinforcement: High strength textile fabric

Cover: Black, smooth (wrapped finish) SBR/NR/EPDM blended rubber; Abrasion, Ozone, Oil and Weather resistant.

Branding: Continuous transfer. Example: "S-SERIES PLANT MASTER 600 HD 1/2" 600 PSI (41 BAR)".



PRODUCT CODE	Size	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (METER)
8-SMP-W600-HD	8	1/2	21	600	4:1	100
12-SMP-W600-HD	12	3/4	29	600	4:1	61
16-SMP-W600-HD	16	1	35	600	4:1	61
20-SMP-W600-HD	20	1-1/4	47	600	4:1	61
24-SMP-W600-HD	24	1-1/2	54	600	4:1	61
32-SMP-W600-HD	32	2	68	600	4:1	61
40-SMP-W600-HD	40	2-1/2	85	600	4:1	61
48-SMP-W600-HD	48	3	98	600	4:1	61
64-SMP-W600-HD	64	4	—	600	4:1	61

MULTIPURPOSE HOSE (AIR, WATER, OIL)

SMP-300 (300 PSI)

Recommended For: Delivery of gasoline, diesel and fuel-oil with aromatic content up to 50%; Seawater, Mud and General

Temperature Range: -4 °F to +185 °F (-20 °C to +85 °C)

Tube: Black NBR Rubber

Reinforcement: High strength textile braider

Cover: Red, smooth (wrapped finish) CR/NBR Rubber: Abrasion, Ozone, Oil and Weather resistant.

Branding: Continuous transfer. Example: "S-SERIES PLANT MASTER PLUS 300 1/4" 300 PSI (20 BAR)".



PRODUCT CODE	Size	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (METER)
4-SMP-300	4	1/4	13	300	3:1	100
6-SMP-300	6	3/8	16.7	300	3:1	100
8-SMP-300	8	1/2	20	300	3:1	100
12-SMP-300	12	3/4	27	300	3:1	100
16-SMP-300	16	1	36	300	3:1	100
20-SMP-300	20	1-1/4	43.5	300	3:1	61
24-SMP-300	24	1-1/2	50	300	3:1	61
32-SMP-300	32	2	63.5	300	3:1	61