



**SCH-200SD-HD (200 PSI)**

**Recommended For:** Mandrel built rubber hose with compounded cross-linked polyethylene tube. It can handle a wide range of chemicals, petroleum products (including aromatics) and oils.  
**Temperature Range:** -40°F to +199°F (-40°C to +93°C)  
**Tube:** Translucent, smooth, cross-linked polyethylene  
**Reinforcement:** High strength synthetic cord plus 2 helix wire

**Cover:** Black, Mandrel, Corrugated (wrapped finish)  
**Branding:** Continuous transfer. Example: "S-SERIES CHEM MASTER 200SD HD 3/4" 200 PSI (14 BAR)".



PRODUCT CODE	Size	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (METER)
12-SCH-200SD-HD	12	3/4	32	200	4:1	61
16-SCH-200SD-HD	16	1	38	200	4:1	61
20-SCH-200SD-HD	20	1-1/4	45	200	4:1	61
24-SCH-200SD-HD	24	1-1/2	52	200	4:1	61
32-SCH-200SD-HD	32	2	65	200	4:1	61

**MULTIPURPOSE HOSE (AIR, WATER)**

**SMP-W300 (300 PSI)**

**Recommended For:** Mandrel built lightweight air hose suitable for a variety of general purpose in industries, construction sites and mines . (1/4"-3/8" non-mandrel built)  
**Temperature Range:** -4°F to +185°F (-20°C to +85°C)  
**Tube:** Black SBR/NR Blend Rubber  
**Reinforcement:** High strength textile braider

**Cover:** Black SBR/NR Blend Rubber, Smooth, Abrasion; Ozone and Weather Resistant.  
**Branding:** Continuous transfer. Example: "S-SERIES PLANT MASTER 300 1/4" 300 PSI (20 BAR)".



PRODUCT CODE	Size	ID (INCH)	OD (MM)	WP (PSI)	SAFETY FACTOR	LENGTH (METER)
4-SMP-W300	4	1/4	13	300	3:1	100
6-SMP-W300	6	3/8	16.7	300	3:1	100
8-SMP-W300	8	1/2	20	300	3:1	100
12-SMP-W300	12	3/4	27	300	3:1	100
16-SMP-W300	16	1	36	300	3:1	100
20-SMP-W300	20	1-1/4	44	300	3:1	61
24-SMP-W300	24	1-1/2	50	300	3:1	61
32-SMP-W300	32	2	63	300	3:1	61