

SSE

PRODUCTOS QUÍMICOS | CHEMICAL

Descripción

Gassoflex SSE es recomendada para la impulsión y/o aspiración de una gran variedad de productos químicos con un buen comportamiento con el PP tales como ácidos, ácidos grasos, alcalinos y disolventes incluso en ambientes corrosivos. Es apta para el uso en carga y descarga de camiones cisternas, vagones, en plantas y aplicaciones marinas.

Construcción

- Espiral interior: Acero Inoxidable 316 (S)
- Espiral exterior: Acero Inoxidable 316 (S)
- Forro interior: Polipropileno PP (E)
- Cubierta: Tejido Poliester / PVC

Características

- Normas: EN 13765:2018
- Gama temperatura: -30 °C a +100 °C
- Factor seguridad: 5:1 (1"-10"), 4:1 (12")
- Vacío: 0,9 bar
- Longitud rollos: 30 m. Otra consultar.

Description

Gassoflex SSE is recommended for delivery and / or aspiration of a great variety of chemical products with a good behavior with PP such as acids, fatty acids, alkaline and solvents even in corrosive environments It is suitable for use in loading and unloading of tank trucks, wagons, in plants and Marine applications.

Construction

- Inner Wire spiral: Stainless Steel 316 (S)
- Outer Wire spiral: Stainless Steel 316 (S)
- Inner Lining: Polypropylene (E)
- Cover: PVC Coated Polyester Cloth

Features

- Norms: EN 13765:2018
- Temperature range: -30 °C a +100 °C
- Safety factor: 5:1 (1"-10"), 4:1 (12")
- Vacuum: 0,9 bar
- Length coils: 30 m. Other under request.



Datos técnicos / Tecnical data

SSE STANDARD DUTY								MARINE OR HEAVY DUTY			
IN D	Ø in	1	1 1/2	2	2 1/2	3	4	6	8	10*	12**
BR	Ø mm	68	100	150	190	250	320	497	740	920	1.150
W	⚖ Kg/m	0,70	1,25	1,70	2,30	3,10	5,71	12,49	22,30	25,90	28,00
CODE	⊗ 14 bar/ 203 psi	•	•	•	•	•	•	•	•	•	
CODE	⊗ 10 bar/ 145 psi				•	•	•				
CODE	⊗ 10,5 bar/ 152 psi				•	•	•				•

* Máx. 28 m. ** Máx. 25 m